

@adbiogas #UKADBiogas

HOW PRE-TREATMENT REDUCES CONTAMINATION AND AIDS DIGESTION

LUIS VERGARA

TECHNICAL DIRECTOR
ULTRAWAVES REACTORS

How pre-treatment reduces contamination and aids digestion

4th July 2013, Purple Seminar Theatre

ULTRASONIC DISINTEGRATION OF THE BIOMASS TO BOOST ANAEROBIC DIGESTION EFFICIENCY



INDEX

1. Ultrasound engineering
2. Anaerobic digestion application
3. References

1. ULTRASOUND ENGINEERING


What is ultrasound?

- A wave is a disturbance travelling through a medium
- Sound is a wave where excited magnitude is pressure
- Ultrasound (US) is a sound wave where the frequency is beyond 20 kHz
- With adequate frequencies and intensities strong **ultrasonic cavitation** is produced

1. ULTRASOUND ENGINEERING


Ultrasonic cavitation

- Forceful implosion takes place and high energy is delivered
- Despite the extreme conditions inside the bubbles the US reactor works under normal T & P



1. ULTRASOUND ENGINEERING


Effect on the biomass



1. ULTRASOUND ENGINEERING

The ultrasonic reactor

- 5 oscillators (1 kW each)
- Reactor volume 30 l
- Frequency 20 kHz & intensity 25 to 50 W/cm²
- Sonication dose 1 to 9 kWh/m³
- Sizes 1.5 x 1.1 x 0.35 m
- Scalable to all ADF sizes by multiple reactors configuration



1. ULTRASOUND ENGINEERING

Transferring energy to the sludge



New sonotrode


Sonotrode after
1.5 to 2 years



2. ANAEROBIC DIGESTION APPLICATION

Process

- Biomass to be treated is between 30 and 50% of the wet flow
- US dose $\approx 4 \text{ kWh/m}^3$ to reach aggregates breakdown
- Readily biodegradable materials and enzymes are released
- Hydrolysis step is highly intensified
- The organic fraction is further degraded



2. ANAEROBIC DIGESTION APPLICATION

An example of common sizing

- Wet solids: 25 - 30 ton WS/d
- Dry solids content $\approx 20\%$
- Dry solids: 5 - 6 ton DS/d
- Dry solids (per year): 1,825 - 2,190 ton DS/y
- Plant capacity: 500 kW_{el}

It is only necessary a 5 kW US unit for each 500 kW_{el} of plant size...!!!

2. ANAEROBIC DIGESTION APPLICATION

Typical results obtained

- Increase in Volatile Solids degradation: 10 - 20%
- Increase in biogas production: 10 - 20% ⁽¹⁾
- Increase in methane content: 1 - 2%
- Decrease in viscosity: 15 - 25%
- Substrate saving: 10 - 20% ⁽²⁾ (1 or 2 is reached)

A 500 kW_{el} plant is optimised up to reach an extra of 50 - 100 kW_{el}
with only 5 kW of US meaning a big net power production...!!!

Ultrasonic disintegration of the biomass to boost anaerobic digestion efficiency


2. ANAEROBIC DIGESTION APPLICATION

Tools: samples sonication & BMP tests



2. ANAEROBIC DIGESTION APPLICATION

Installation in ADFs



- Place to install the ultrasonic reactor depends on several factors
- Some factors are DS %, viscosity, biomass structure and type of AD process

Ultrasonic disintegration of the biomass to boost anaerobic digestion efficiency

3. REFERENCES

Bordesholmerland FBP



3. REFERENCES

Bordesholmerland FBP

Initial conditions

- 2 parallel lines (2 x 537 kW_{el}) to produce 2 x 6,150 m³/d biogas @ 50% in methane content
- 2 main & 2 post digesters with 2 storage tanks (2,500 m³ each)
- 2 x 25 ton maize/d fed to be digested within 90 d HRT

Goal


- Reduce amount of substrate

3. REFERENCES

Bordesholmerland FBP

US installation

- Sonication of 36 m³/d @ 3.3 kWh/m³ in line 2




3. REFERENCES

Bordesholmerland FBP

Results

- 4 ton/d less substrate (- 17%)
- 2 % increase in methane content
- Decrease in viscosity



Ultrasonic disintegration of the biomass to boost anaerobic digestion efficiency

3. REFERENCES

Mariks FWBP



3. REFERENCES

Mariks FWBP

Initial conditions

- 2 main & 1 post digester (1,800 m³ each) and 1 storage tank (5,000 m³)
- 700 kW_{el} power production & methane content ca. 58%
- 73 ton/d fed to be digested within 40 d HRT

Goal


- Increase biogas production

3. REFERENCES

Mariks FWBP

US installation



- Sonication of 34 m³/d @ 3.5 kWh/m³ from post to main digester



3. REFERENCES

Mariks FWBP

Results



- kW_{el} power increased in 13% and volatile solids concentration in post digester decreased by 8%

3. REFERENCES

Bamberg WwTW



3. REFERENCES

Bamberg WwTW

Initial conditions

- 220,000 PE capacity by design was overloaded up to reach a treatment of 330,000 PE
- 150 m³/d of primary sludge and 250 m³/d of TWAS
- 35% average in VS degradation @ HRT of 18 d

Goal


- Achieve a minimum of 45% in VS degradation

3. REFERENCES

Bamberg WwTW


US installation

- Sonication of 60 m³/d of the TWAS @ 4 kWh/m³



3. REFERENCES

Bamberg WwTW



3. REFERENCES

Bamberg WwTW

Results

- VS degradation increased from 34 to 50% (average)
- Reduction of the VS in the digested sludge from 60 to 54%
- Significantly increase in biogas production (+ 30% average)
- A new anaerobic digester construction was **avoided** what meant a saving of 1.5 million €

Thank you

Luis Vergara

Technical Director

luis@ultrawaves.co.uk